


Product number: 006940

 Niet meer leverbaar



Description:	LEXIC DXH MCBS 3P C 16A
Brand:	Legrand
Series:	Lexic DX-H
Product Class:	Installatieautomaat
Price :	Price on request
Start Date:	
Discount Group:	I1
Net Weight (kg):	0,453

## Features

Release characteristic:	C	Number of poles (total):	3
Nominal rated current (A):	16	Nominal rated voltage (V):	400
Voltage type:	AC	Current limiting class:	3
Concurrently switching N-neutral:	No	Pollution degree:	3
Width in number of modular spacings:	3	Built-in depth (mm):	44
Additional equipment possible:	Yes	Degree of protection (IP):	IP2X
Width (mm):	53.4	Height (mm):	83
Depth (mm):	76	Rated short-circuit breaking capacity Icn EN 60898 at 230 V (kA):	10
Rated short-circuit breaking capacity Icn EN 60898 at 400 V (kA):	10	Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 (kA):	25
Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 (kA):	25	Frequency (Hz):	50 - 60
Suitable for flush-mounted installation:	No		

Prices are valid for the Dutch market. All prices are gross, excluding VAT. Technical and / or price changes and mistakes are possible.